

Aqua Mix® Poultice Stain Remover



1. Product Name

Aqua Mix® Poultice Stain Remover

2. Manufacturer

Custom Building Products
Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

A dual purpose, non-acidic stain remover. It is an absorptive clay that is designed to remove deep-set oil and grease stains. It is also a fine abrasive cleaning powder that removes stubborn surface stains and light grout haze.

Key Features

- Effectively removes deep-set oil and grease stains
- Safe, nonacidic, abrasive cleaning powder
- Excellent cleaning additive

Uses

All honed, unpolished natural stone (such as granite, limestone, marble, slate, and travertine), porcelain, quarry, Saltillo, terra-cotta, cement pavers, masonry surfaces, and other porous tile and grout

Limitations to the Product

- Do not allow product to come in contact with any non-recommended surface
- Light abrasive action or high RPMs on the surface of some marbles may dull the high-polished finish

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

FOR REMOVING DEEP-SET OIL AND GREASE STAINS: Read entire label before using. Mix Poultice Stain Remover powder with water to form a thick, pliable paste. Quantity of Poultice Stain

Remover needed will depend on size of stain. Apply a 1/4" (6 mm) thick layer of paste directly over stain with at least a 1" (25 mm) overlap beyond edge of stain. Cover with plastic or wax paper. Poke a few very small holes in plastic cover to allow for minimum air exposure. Allow paste to stand on stain for 24 to 48 hours. Remove Poultice Stain Remover with plastic spatula or plastic putty knife and wash off residue with clean water. Repeat procedure if necessary. If area darkens from absorbed moisture, it should dry completely within 5 to 7 days.

FOR REMOVING SURFACE STAINS AND GROUT RESIDUE: Read entire label before using. Protect surrounding areas from splattering to minimize cleanup. Pre-wet a manageable area of the surface with water, approximately 10 ft (1 M) and sprinkle Poultice Stain Remover onto the area mixing into a thin slurry. If surface is vertical, mix slurry in a container and apply to pre-wet surface. Agitate by hand or with low RPM (175-350 RPM) buffer using a white nylon scrub pad. Keep surface wet throughout buffing process. Remove Poultice Stain Remover solution with clean towels or sponge and rinse twice with clean water. A wet/dry vacuum may be used. Rinse with clean water and buff dry with clean towels

NOTE: Poultice Stain Remover is an excellent additive that will boost the cleaning power of many of the Aqua Mix® cleaners such as Phosphoric Acid Substitute, Heavy-Duty Tile & Grout Cleaner, and Stone Deep Clean.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains barium sulfate and silicic acid. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

4. Size & Availability

Location	Item Code	Size	Package
USA	010864	6 Lb. (2.72 kg)	Jar
Canada	C010861	3/4 Lb. (.34 kg)	Jar

5. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details and complete warranty information, visit custombuildingproducts.com

6. Product Maintenance

Properly installed product requires no special maintenance.

Aqua Mix® Poultice Stain Remover

7. Technical Services Information

For technical assistance contact Custom® Building Products.

8. Filing System

Additional product information is available from the manufacturer upon request.
