

Aqua Mix® Sealer's Choice® Gold



1. Product Name

Aqua Mix® Sealer's Choice® Gold

2. Manufacturer

Custom Building Products

Technical Services
10400 Pioneer Boulevard, Unit 3
Santa Fe Springs, CA 90670
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Fax: 800- 200-7765
Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

A premium, no-sheen, natural look, water-based, penetrating sealer formulated to provide maximum stain protection, especially in food preparation and serving areas. Allows moisture vapor transmission. Rapid Cure Formula protects in less than 4 hours. May also be used as a pre-grouting sealer.

Key Features

- Premium sealer for stone, tile and grout
- Maximum stain resistance
- Water-based formula
- For interior and exterior use

Limitations to the Product

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, scrub with [Aqua Mix NanoScrub](#) and a white nylon pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

Technical Chart

Property Test Method Typical Results

Stain Resistance CTI-072 Excellent
pH 8

Complies with all Federal EPA and SCAQMD standards for VOC

4. Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. New installations need to be dry 48 hours before application. Protect surrounding surfaces. Test product in an inconspicuous area to ensure desirable results.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Read entire label before using. Apply using a paint pad applicator, sponge or brush. Allow it to penetrate for up to 5 minutes. Wipe surface completely dry using clean, dry cotton, paper or microfiber towels after each application. Porous surfaces may require additional applications. Conduct a test to see if surface is completely sealed after 2 hours by applying drops of water on the surface. If it penetrates, an additional application is required.

Cleaning of Equipment

Clean tools with soap and water immediately after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear appropriate skin and eye protection equipment and ventilate area when spraying. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

5. Size & Availability

Location	Item Code	Size	Package
USA	030881	1 pt (473 ml)	Bottle
USA	030882-4	1 qt (946 ml)	Bottle
USA	030883	1 gallon (3.8 L)	Bottle
USA	030884	5 gallon (19 L)	Pail
Canada	C030881	1 pt (473 ml)	Bottle
Canada	C030882-4	1 qt (946 ml)	Bottle
Canada	C030883	1 gallon (3.8 L)	Bottle
Canada	C030884	5 gallon (19 L)	Pail

6. Product Warranty

Custom® Building Products warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country or territory to another. For details

Aqua Mix® Sealer's Choice® Gold

and complete warranty information, visit [/reference-library/warranties.aspx](#)

7. Product Maintenance

Aqua Mix® Concentrated Stone & Tile Cleaner or AquaKleen® or AquaShield® Cleaner & Resealer is recommended for routine spray and wipe cleaning and resealing.

8. Technical Services Information

For technical assistance contact Custom® Building Products or visit [custombuildingproducts.com](#).

9. Filing System

Additional product information is available from the manufacturer upon request.
